

EPS Code 1014111-0.5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	0.5
Packaging Quantity	1

EPS Code

1014111-2



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	2
Packaging Quantity	1

EPS Code

1041310-1



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1

EPS Code

1041310-2



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1

EPS Code

1041310-3



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1

EPS Code

1041310-1



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1

EPS Code

1014111-10



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	10
Packaging Quantity	1

EPS Code 1014111-15



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	15
Packaging Quantity	1

EPS Code

1014111-20



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	20
Packaging Quantity	1

EPS Code

1014111-2



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	2
Packaging Quantity	1

EPS Code

1014111-3



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	3
Packaging Quantity	1

EPS Code

1014111-5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	5
Packaging Quantity	1

EPS Code

1014111-8



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	8
Packaging Quantity	1

EPS Code 1014121-0.5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	0.5
Packaging Quantity	1

EPS Code 1014121-0.15



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	0.15
Packaging Quantity	1

EPS Code 1014121-1.5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1.5
Packaging Quantity	1

EPS Code

1014121-1



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1

EPS Code

1014121-2



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	2
Packaging Quantity	1

EPS Code

1014121-3



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	3
Packaging Quantity	1

EPS Code

1014121-5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	5
Packaging Quantity	1

EPS Code 1014431-0.5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	0.5
Packaging Quantity	1

EPS Code 1014431-1.5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1.5
Packaging Quantity	1

EPS Code 1014431-10



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	10
Packaging Quantity	1

EPS Code

1014431-12



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	12
Packaging Quantity	1

EPS Code

1014431-15



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	15
Packaging Quantity	1

EPS Code 1014431-1



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1

EPS Code

1014431-20



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	20
Packaging Quantity	1

EPS Code

1014431-25



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	25
Packaging Quantity	1

EPS Code

1014431-2



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	2
Packaging Quantity	1

EPS Code

1014431-30



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	30
Packaging Quantity	1

EPS Code 1014431-3



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	3
Packaging Quantity	1

EPS Code 1014431-5



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	5
Packaging Quantity	1

EPS Code 1014431-7



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	6A
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	S/FTP
Nom OD and gauge	26 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	7
Packaging Quantity	1

EPS Code

1014111-1



Product Specifications

Product Type	Twisted pair patch cord
ANSI TIA Category	5e
Test Standard	ISO/IEC 11801:2011, TIA-568-2.D
Cable Type	U/UTP
Nom OD and gauge	24 AWG
Environmental space	Low Smoke Zero Halogen (LSZH)
ROHS compliant	yes
Installation temperature	-25 °C to +70 °C

Ordering Information

Color	blue
Packing Length in Meter	1
Packaging Quantity	1