

EPS Code 1014111-0.5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 0.5 |
| Packaging Quantity | 1 |

EPS Code 1014111-10



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 10 |
| Packaging Quantity | 1 |

EPS Code 1014111-15



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 15 |
| Packaging Quantity | 1 |

EPS Code 1014111-1



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 1 |
| Packaging Quantity | 1 |

EPS Code 1014111-20



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 20 |
| Packaging Quantity | 1 |

EPS Code 1014111-2



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 2 |
| Packaging Quantity | 1 |

EPS Code 1014111-3



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 3 |
| Packaging Quantity | 1 |

EPS Code 1014111-5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 5 |
| Packaging Quantity | 1 |

EPS Code 1014111-8



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 5e |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 8 |
| Packaging Quantity | 1 |

EPS Code 1014121-0.5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 0.5 |
| Packaging Quantity | 1 |

EPS Code 1014121-0.15



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 0.15 |
| Packaging Quantity | 1 |

EPS Code 1014121-1.5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 1.5 |
| Packaging Quantity | 1 |

EPS Code 1014121-1



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 1 |
| Packaging Quantity | 1 |

EPS Code 1014121-2



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 2 |
| Packaging Quantity | 1 |

EPS Code 1014121-3



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 3 |
| Packaging Quantity | 1 |

EPS Code 1014121-5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6 |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | U/UTP |
| Nom OD and gauge | 24 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 5 |
| Packaging Quantity | 1 |

EPS Code 1014431-0.5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 0.5 |
| Packaging Quantity | 1 |

EPS Code 1014431-1.5




Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 1.5 |
| Packaging Quantity | 1 |

EPS Code 1014431-10



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 10 |
| Packaging Quantity | 1 |

EPS Code 1014431-12



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 12 |
| Packaging Quantity | 1 |

EPS Code 1014431-15



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 15 |
| Packaging Quantity | 1 |

EPS Code 1014431-1




Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 1 |
| Packaging Quantity | 1 |

EPS Code 1014431-20



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 20 |
| Packaging Quantity | 1 |

EPS Code 1014431-25




Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Lenght in Meter | 25 |
| Packaging Quantity | 1 |

EPS Code 1014431-2



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 2 |
| Packaging Quantity | 1 |

EPS Code 1014431-30



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 30 |
| Packaging Quantity | 1 |

EPS Code 1014431-3




Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 3 |
| Packaging Quantity | 1 |

EPS Code 1014431-5



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 5 |
| Packaging Quantity | 1 |

EPS Code 1014431-7



Product Specifications

| | |
|--------------------------|---------------------------------|
| Product Type | Twisted pair patch cord |
| ANSI TIA Category | 6A |
| Test Standard | ISO/IEC 11801:2011, TIA-568-2.D |
| Cable Type | S/FTP |
| Nom OD and gauge | 26 AWG |
| Environmental space | Low Smoke Zero Halogen (LSZH) |
| ROHS compliant | yes |
| Installation temperature | -25 °C to +70 °C |

Ordering Information

| | |
|-------------------------|------|
| Color | blue |
| Packing Length in Meter | 7 |
| Packaging Quantity | 1 |